RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL, GAS AND GEOTHERMAL RESOURCES

REPORT OF PROPERTY AND WELL TRANSFER

Field or county Wilmington		District - Cypress (D1)
Former owner Four Teams Oil Production & Exploration Company, Inc.	Opcode: F1535	Date August 12, 2010

Name and location of well(s)

SEE ATTACHMENT

Description of the land upon which the well(s) is (are) located

See Attachment

Date of transfer, sale, assignment, conveyance, or exchange 8/1/2010	New Owner E & B Natural Resources Management Corp. Address 1600 Norris Road Bakersfield, CA 93308	Operator code E0100	Type of Organization Corporation Telephone No. (661) 679-1700

Reported by OG30A received 8/11/2010 signed by both parties

Confirmed by. Same as above

New operator new status (status abbreviation) PA	Request Designation of Agent Jeffrey Blesener
Old operator new status (status abbreviation) PA	Remarks See Operator File

Deputy Supervisor Kenneth Carlson	Signature FOR Chris McCullough, Associate Engineer

OPERATOR STATUS ABBREVIATIONS

PA - Producing Active	**FORM AND RECORD CHECK LIST**						
NPA - No Potential Active	**Form or record**	**Initials**	**Date**	**Form or record**	**Initials**	**Date**
PI - Potential Inactive	Form OGD121			Map and Book		
NPI - No Potential Inactive	Well records			Lease Files		
Ab - Abandoned or No More Wells	New well cards			Well Stat		

OGD156 (Modified 1/00)

E & B Natural Resources Mgmt. Corp.

WELL TRANSFER NOTICE

On 12-21-98
XL OPERATING COMPANY
transferred
all wells in the Wilmington field
(See OGD156 dated December 21, 1998 for complete list)
to

FOUR TEAMS OIL PROD. & EXPL., INC.

WELL TRANSFER NOTICE

Effec February 7, 1997

XTRA ENERGY CORPORATION

TRANSFERRED

all wells Wilmington

(See Operator File for Complete List)

TO

XL OPERATING COMPANY

SEE OGD156 DATED 02-7-97

DIVISION OF OIL AND GAS

CHECK LIST - RECORDS RECEIVED AND WELL STATUS

Company Vlra Energy Corp. Well No. "UNF-E" 50

API No. 037-22884 Sec. 29, T. 4S, R. 13W, SB B.&M.

County _____ Field Wilmington

RECORDS RECEIVED	DATE
Well Summary (Form OG100)	10/26/83 ②
History (Form OG103)	10/26/83 ②
Core Record (Form OG101)	
Directional Survey	10/26/83 ②
Sidewall Samples	
Other	
Date final records received	
Electric logs: Induct E. Log 2+5 10/26/83 ②	

STATUS		STATUS	
Producing - Oil	✓	Water Disposal	
Idle - Oil		Water Flood	
Abandoned - Oil		Steam Flood	
Drilling - Idle		Fire Flood	
Abandoned - Dry Hole		Air Injection	
Producing - Gas		Gas Injection	
Idle - Gas		CO_2 Injection	
Abandoned - Gas		LPG Injection	
Gas-Open to Oil Zone		Observation	
Water Flood Source			

DATE 7-23-83

RECOMPLETED _____

REMARKS _____

ENGINEER'S CHECK LIST

1. Summary, History, & Core record (dupl.) ✓ ✓
2. Electric Log ✓
3. Operator's Name
4. Signature
5. Well Designation
6. Location
7. Elevation
8. Notices ✓
9. "T" Reports ✓
10. Casing Record
11. Plugs
12. Surface Inspection
13. Production
14. E Well on Prod. Dir. Sur. ✓

CLERICAL CHECK LIST

1. Location change ____ (F-OGD165) _____
2. Elevation change ____ (F-OGD165) _____
3. Form OGD121 _____
4. Form OG159 (Final Letter) _____
5. Form OGD150b (Release of Bond) _____
6. Duplicate logs to archives _____
7. Notice of Records due (F-OGD170) _____

TD 3936'

Update Center
1/6/84 cm

RECORDS NOT APPROVED

Reason: _____

RECORDS APPROVED 11-18-83

RELEASE BOND _____

Date Eligible _____

(Use date last needed records were received.)

MAP AND MAP BOOK @ 128

LONG BEACH OFFICE - USE REVERSE SIDE

OGD2 (12/80/DWRR/5M)

CHECK LIST - RECORDS RECEIVED AND WELL STATUS

Well No._____

API No._____ Sec._____, T._____, R._____, _____B.&M.

WORK PERFORMED

Drill_____ Redrill_____ Deepen_____

Plug_____ Alter Casing_____

Water Flood_____ Water Disposal_____

Abandon_____

Other_____

STATUS DATE

Producing_____

Recompleted Producing_____

Water Flood_____

Water Disposal_____

Abandoned_____

Other_____

MAP AND BOOK_____ Engineer_____

RECORDS FILED AND DATE Clerk_____

Summary_____

Log and Core_____

History_____

E-log_____

_____

Directional Survey_____

Other_____

(Check records for signature and correct name of operator or well, section, township, range, and field.)

Location_____ Notice states_____

_____

_____

_____

_____

Elevation_____ Notice states_____

_____

_____

_____

Production Reports_____

_____

(If production reports not received, make notation and inform Senior Stenographer when received.)

RECORDS & REQUIREMENTS CHECKED Engineer_____

_____

_____

_____

_____

_____

_____

Surface Inspection_____

Data Needed_____

Request Records_____ OGD170_____

Correct records_____ OGD165_____
(Specify)

CARDS_____

BOND_____

Hold_____ Reason_____

Release_____ Date Eligible_____ OGD150_____

(Check One)

End premium year _____

Release requested _____

Bond superseded _____

Well abandoned _____

Environmental Inspection_____ Engineer_____

FINAL LETTER_____ OG159_____

and

File cleared _____ OGD121_____

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL AND GAS

API No. 037-22884

WELL SUMMARY REPORT

Operator	Well				
Xtra Energy Corporation	~~B-50~~ "WNF-I" 50				
Field	**County**	**Sec.**	**T.**	**R.**	**B.&M.**
Wilmington	Los Angeles	29	4S	13W	S.B.

Location (Give surface location from property or section corner, street center line and/or California coordinates)
497' North & 827' East at right angles from the centerlines of Main St. and Lomita Blvd. in the city of Carson.

Elevation of ground above sea level

Commenced drilling (date)
July 7, 1983

Completed drilling (date)
July 23, 1983

Commenced producing (date)
August 24, 1983

☐ Flowing ☒ Pumping
☐ Gas lift

Name of producing zone(s)
Ranger

Total depth

(1st hole)	(2nd)	(3rd)
3936'		

Present effective depth
3936'

Junk

Depth measurements taken from top of:
☐ Derrick Floor ☐ Rotary Table ☒ Kelly Bushing
Which is 22 feet above ground

GEOLOGICAL MARKERS	DEPTH
"F" Marker	3812'

Formation and age at total depth

	Clean Oil (bbl per day)	Gravity Clean Oil	Percent Water Including emulsion	Gas (Mcf per day)	Tubing Pressure	Casing Pressure
Initial Production	2	14	99.2	0	15	48
Production After 30 days	14	14	96.0	0	10	45

CASING RECORD (Present Hole)

Size of Casing (API)	Top of Casing	Depth of Shoe	Weight of Casing	Grade and Type of Casing	New or Second Hand	Size of Hole Drilled	Number of Sacks or Cubic Feet of Cement	Depth of Cementing (if through perforations)
10 3/4"	Surf	600'	40.5#	K-55	New	14 3/4"	450 sx	
7"	Surf	3812'	23#	K-55	New	9 7/8"	311 sx	
5"	3760'	3936'	18#	K-55	New	9 7/8"	- 12" Gvl Packed	

PERFORATED CASING (Size, top, bottom, perforated intervals, size and spacing of perforation and method.)
5" Wire wrapped Johnson "Pipeless" screen liner w/ 0.012" slots.
Gravel packed w/ 245 sx 20-40 mesh gravel. See attached liner detail.

Was the well directionally drilled? If yes, show coordinates at total depth
☒ Yes ☐ No 932' South & 1468' East of Surf. location TVD = 3354'

Electrical log depths
3936' - 600'

Other surveys
None

In compliance with Sec. 3215, Division 3 of the Public Resources Code, the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Name	Title	
Xtra Energy Corporation	Senior Vice President	
Address	**City**	**Zip Code**
2501 Cherry Avenue Suite 270	Signal Hill . CA	90806
Telephone Number	**Signature**	**Date**
(213) 424-8549	John D. Carmichael	10-24-83

SUBMIT IN DUPLICATE

OG100 (3/82/GSR1/5M)

XTRA ENERGY CORP.

LINER DETAIL

WELL NO. 50



GRAVEL PACKED W/ 245 SX OF 20-40 MESH GRAVEL.
CALCULATED VOL 848X.

JDC/7-83

SUBMIT IN DUPLICATE

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION

DIVISION OF OIL AND GAS

History of Oil or Gas Well

Operator Xtra Energy Corp. Field Wilmington County Los Angeles
Well (50) "WOF-I" 50, Sec. 29, T 4S, R 13W, S.B B. & M.
A.P.I. No. 037-22884 Name John D. Carmichael (Person submitting report) Title Senior Vice President (President, Secretary or Agent)
Date July 25, 1983

Signature John D. Carmichael

2501 Cherry Avenue Suite 270 Signal Hill CA 90806 (213) 424-8549
(Address) (Telephone Number)

History must be complete in all detail. Use this form to report all operations during drilling and testing of the well or during redrilling or altering the casing, plugging, or abandonment with the dates thereof. Include such items as hole size, formation test details, amounts of cement used, top and bottom of plugs, perforation details, sidetracked junk, bailing tests and initial production data.

Date	
7-8-83	MI fr Well # 51, RU, spud in @ 6 A.M., drld & surveyed 14-3/4" hole fr 60' to 485' @ 6 A.M. SS @ 390', bulls eye! CB mud wt 73#/CF, Vis 47", WL 7.2 cc, Cake 2/32", Solids 12.0%, Sand 1.0%, 1600 ppm Cl, Oil 2.0%, pH 10.0.
7-9-83	Cont'd drlg & surveying 14-3/4" hole fr 485' 615', C & C mud, wipe hole, POH, H & H Tong Serv ran 602' of 10-3/4", K-55, 40.5# csg, shoe @ 600', B-J pmpd 20 bbls dye wtr, 300 sx "G" cmt mxd 1:1:4, 150 sx "G" neat cmt, all cmt mxd w/2% $CaCl_2$, good circ thru job but no cmt rtns, total slurry 791 CF, pmpd 50 sx top job thru 90' of 1" tbg, good rtns, CIP @ 5 P.M. WOC until 8 P.M., cut off 28.00' of 10-3/4" csg, weld on 7" csg head, instld BOP, RIH w/9-7/8" drlg assy, tst csg & BOP w/1000 psi, OK by DOG @ 6 A.M. CB mud wt 72#/CF, Vis 43", WL 5.6 cc, Cake 2/32", Solids 10.0%, Sand 0.25%, 1750 ppm Cl, Oil 0.0%, pH 11.9.
7-10-83	C/O cmt fr 585', D/O shoe @ 600', C/O to 615', drld 9-7/8" hole to 625', POH, RIH w/Dynadril, drld & surveyed 9-7/8" hole fr 625' to 1263', POH w/Dynadril, RIH w/angle bldg assy, C/O Dynadril run, drld & surveyed fr 1268' to 1682' @ 6 A.M. SS @ 1652', 36°, S 56° 30' E, hole is 6' rt & 25' lo. CB mud wt 72#/CF, Vis 45", WL 4.9 cc, Cake 2/32", Solids 10.0%, Sand 0.25%, 1400 ppm Cl, Oil -, pH 10.3.
7-11-83	Cont'd drlg 9-7/8" hole fr 1682' to 1714', RT for locked assy, drld to 2134', RT for angle dropping assy, drld to 2641', RT for Dynadril, now orientating Dynadril @ 6 A.M. SS @ 2641', 39° S 54° 30' E, hole is 34' rt & 32' hi. CB mud wt 73#/CF, Vis 47", WL 4.7 cc, Cake 2/32", Solids 11.0%, Sand 0.25%, 1350 ppm Cl, Oil -, pH 9.6.
7-12-83	Dynadrld 9-7/8" hole fr 2641' to 2742', RT for angle dropping assy, drld to 2827' brk survey wire, RT to retrieve tools, cont'd drlg to 3167' @ 6 A.M. SS @ 3137', 37°, S 61°E, hole is 22' rt & 25' hi.CB mud wt 73#/CF, Vis 50", WL 4.5 cc, Cake 2/32", Solids 11.0%, Sand 0.25%, 1300 ppm Cl, Oil -, pH 10.0, Rotating time 14.0 hours.

7-13-83 Cont'd drlg & surveying 9-7/8" hole fr 3167' to 3501', RTCB, drld to 3830' @ 6 A.M. SS @ 3744', 34°30', S 59°30' E, hole is 2.5' rt, 12' hi. CB mud wt 75#/CF, Vis 50", WL 4.6 cc, Cake 2/32", Solids 12.0%, Sand 0.25%, 1300 ppmCl, Oil 0.0%, pH 9.8. Rotating time 19.5 hours.

7-14-83 Cont'd drlg & surveying 9-7/8" hole fr 3830' to 3921', made wiper trip to 600', C & C mud for log, POH, D-A unable to go below 3836' w/sonde, ran IES log to 600', RIH w/9-7/8" drlg assy, reamed fr 3836' to 3921', drld to 3936', C & C mud, D-A ran IES fr 3936' to 3700', RIH to 3936', C & C mud for 7" csg @ 6 A.M. SS @ 3921', 33°, S 59° 30' E, hole is 2' low and on line for direction. CB mud wt 74#/CF, Vis 40", WL 4.8 cc, Cake 2/32", Solids 11.5%, Sand 0.25%, 1350 ppm Cl, Oil -, pH 8.8.

7-15-83 POH & LD 4-1/2" DP, H & H Tong Serv ran 104 jts 7", 23#, K-55 Buttress csg, Bkr shoe @ 3812', Bkr FC @ 3737', B-J cmtd w/80 CF mud sweep followed by 211 sx "G" cmt mxd 1:1:4, followed by 100 sx "G" neat cmt, bmpd plg w/1000 psi, CIP @ 4:40 P.M. Rmvd BOP, cut off 28.81' of 7" csg, weld on tbg head, instld & tstd BOP w/1000 psi, OK, RIH w/6-1/4" bit, P/U 3-1/2" DP, fnd cmt @ 3733', now C/O @ 6 A.M. CB mud wt 74#/CF, Vis 51", WL 5.1 cc, Cake 2/32", Solids 11.5%, Sand 0.25%, 1350 ppm Cl, pH 8.9.

7-16-83 C/O cmt fr 3733', FC @ 3737', cmt to 3800', POH, WOC, RIH w/Howco WSO tstr, perf'd 4 1/2" holes @ 3800', set pkr @ 3760', hvy blo, fluid to surf in 29 min, wtr & hvy crude, C & C mud, POH, RIH w/RTTS, set @ 3693', pmpd 100 sx "G" cmt mxd w/2% $CaCl_2$, brk form w/2000 psi @ 4 bbls/min, sqzd to final press of 1300 psi, 100 CF in form, CIP @ 11 P.M., press

7-17-83 D/O to 3802', C & C mud, POH, RIH w/Howco WSO tools, perf'd 4 1/2" holes @ 3802', pkr @ 3759', opn tool 1 hr, POH, WSO approved by DOG, RIH w/6-1/4" bit, D/O shoe @ 3812', C/O to 3936', chng over to Polymer mud, POH, RIH w/King under reamer, opn 9-7/8" hole to 12" fr 3812' to 3936', gauge ream hole, circ cln, POH @ 6 A.M. Polymer mud wt 73#/CF, Vis 39", WL 14.0 cc, Cake - film, Solids 2.9%, Sand - trace, 110,000 ppm Cl, Oil 0.0%, pH 8.8.

7-18-83 Fin POH w/under reamer, RIH w/185' of 5" lnr, well started flowing, unable to run lnr below 3895', POH, LD lnr, RIH w/bit, stopped @ 3859', C/O to 3936', C & C mud @ 6 A.M. Polymer mud wt 73#/CF, Vis 38", WL 13.0 cc, Cake - film, Solids 4.5%, Sand 0.75%, 88,000 ppm Cl, Oil - 0%.

7-19-83 POH, RIH w/King under reamer, regauge hole fr 3812' to 3936', tight hole @ 3834', sand kept running, chng out mud system to 85#/CF $CaCl_2$ polymer, regauge hole, tight @ 3886', cont'd reaming ** circ until hole stabilized, spot hi vis pill, now POH @ 6 A.M. Polymer mud wt 85#/CF, Vis 45", WL 12.0 cc, Cake - film, Solids 1.0%, Sand - trace, 230,000 ppm Cl, Oil -, pH 6.8.

7-20-83 Fin POH, RIH w/5" lnr, shoe @ 3936', Bkr started gvl pkg w/300 psi, press rose to 1100 psi after 35 sx, rvse out, cont'd gvl pkg, press @ 500 psi, slow dn to 2 sx/hr, chkd for wshd lnr & pkr cups OK, cont'd gvl pkg, press rose to 1100 psi after 96 sx, rvse out 5 sx, bk off lnr, total of 91 sx 20-40 mesh gvl, Calc 84 sx, POH w/gvl pkg tools @ 6 A.M. Polymer mud wt 84#/CF, Vis 45", WL 13.0 cc, Cake - film, Solids 1.5%, Sand - trace, 226,000 ppm Cl, Oil - trace, pH 7.0.

7-21-83 RIH w/lead seal, drove over lnr adaptor, top @ 3760', POH, D-A attempt to run gvl pk log, stopped @ 3870', RIH w/OE tbg, C/O snd to btm 3936', P/U, pmpd D-A tool dn, ran gvl log, indicated good gvl pk fr 3870' to btm 3936' w/bridge @ 3860' to 3840', POH, RIH w/ J. B. Nelson perf wshr, wshd fr 3875' to 3792' for 3 hrs, wshd fr 3936' to 3792', no formation snd in mud, no fill in lnr, POH, RIH w/Bkr PC tool to gvl pk thru PC @ 6 A.M. Polymer mud wt 84#/CF, Vis 44", WL 13.2 cc, Cake - film, Solids 2.0%, Sand - trace, 230,000 ppm Cl, Oil - trace, pH 7.1.

7-22-83 Loc & opn PC @ 3766', Bkr gvl pkd thru PC w/154 sx additional 20-40 mesh snd, total of 245 sx, Calc 84 sx, final press 1600 psi, clsd & tstd PC w/1000 psi, circ cln, POH w/PC straddle tool, RIH w/OE DP, D-A RU & ran Photon gvl pk log, indicated 95+% gvl pk, chng over to wtr @ 6 A.M. Polymer mud wt 84#/CF, Vis 42", WL 13.4 cc, Cake - film, Solids 2.0%, Sand

7-23-83 Chng over to wtr, POH & LD 3-1/2" DP, rmve BOP, instld tbg top, RR @ 2 A.M. 7-23-83. RD to move to Well No. 49.

STATE OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL AND GAS

REPORT ON PROPOSED CHANGE OF WELL DESIGNATION

Long Beach, California

October 17, 1983

John D. Carmichael, Agent
XTRA ENERGY CORPORATION
2501 Cherry Avenue, Suite 270
Signal Hill, CA 90806

Your request, dated September 15, 1983, proposing to change the designation of well(s) in Sec. see below, T. 4S, R. 13W, S.B. B. & M., Wilmington field, Los Angeles County, District No. 1, has been received.

The proposed change in designation, in accordance with Section 3203, Public Resources Code, is authorized as follows:

Sec. 19-4S-13W

OLD	NEW DESIGN.		API 037-
8	"WNF-I"	8	22620
10	"WNF-I"	10	22611
18	"WNF-I"	18	22853
19	"WNF-I"	19	22846
20	"WNF-I"	20	22652
23	"WNF-I"	23	22672
26	"WNF-I"	26	22666-01
27	"WNF-I"	27	22673
28	"WNF-I"	28	22674
29	"WNF-I"	29	22648
43	"WNF-I"	43	22682
Sec. 20-4S-13W			
42	"WNF-I"	42	22689
44	"WNF-I"	44	22820

OLD		NEW		API 037-
"American Can"	1	"WNF-I"	12	21433
"	2	"WNF-I"	15	21644
"	3	"WNF-I"	3	21768
"Dasco Unit"	1	"WNF-I"	1	21671
I-14		"WNF-I"	11	22603
"Purex Unit"	1	"WNF-I"	9	21669
"	2	"WNF-I"	5	21753
"	3	"WNF-I"	4	21754
"Sanitation Unit"	1	"WNF-I"	21	21445
Sec. 20-4S-13W				
31	"WNF-I"	31	22767	
33	"WNF-I"	33	22768	
34	"WNF-I"	34	22787	
35	"WNF-I"	35	22795	
36	"WNF-I"	36	22769	
37	"WNF-I"	37	22796	
38	"WNF-I"	38	22752	
39	"WNF-I"	39	22754	

M. G. MEFFERD, State Oil and Gas Supervisor

By _____
FOR V. F. GAEDE, *Deputy Supervisor*

EDP
Update
Conservation Committee
Long Beach Dept. of Oil Properties

OGD 157 (3-79-DWRR-1M)

Sec. 20-4S-13W

OLD	NEW	API 037-
"Shell Unit" 1	"WNF-I" 32	21729
"Shell Unit" 2	"WNF-I" 40	21769

Sec. 29-4S-13W

"Lomita Unit" 1	"WNF-I" 67	22487
49	"WNF-I"49	22886
50	"WNF-I" 50	22884
51	"WNF-I" 51	22885
53	"WNF-I" 53	22874
54	"WNF-I" 54	22871
56	"WNF-I" 56	22865
57	"WNF-I" 57	22815

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION

No. T 183-521

DIVISION OF OIL AND GAS

Report on Operations

SEC. 3606 WELL

John D. Carmichael, Agent
XTRA ENERGY CORPORATION
Box "9"
Signal Hill, CA 90801

Long Beach, Calif.
July 25, 1983

Your operations at well 50, API No. 037-22884,
Sec. 29, T. 4S, R. 13W S.B. B.& M. Wilmington Field, in Los Angeles County,
were witnessed on 7/16/83. G. Muggelberg, Engineer, representative of
the supervisor, was present from 1330 to 1430. There were also present Floyd Millien, Drilling Foreman

Present condition of well: 16" dr 90'; 10-3/4" cem 608'; 7" cem 3812', cp 3800', perf 3802' WSO. TD 3936' (drilling).

The operations were performed for the purpose of testing the 7" shut-off at 3802' with a formation tester.

DECISION: APPROVED

NOTE: DEFICIENCIES TO BE CORRECTED
NONE

DEFICIENCIES CORRECTED
One wet test

CONTRACTOR - Cal Pacific Drilling Co.

GM:csm

cc: Update

S1 CORDOVA
ACTING *State Oil and Gas Supervisor*

By
ACTING *Deputy Supervisor*
V.F. GAEDE

OG109(12-80-15M)

Form OGD8 (8/80) DIVISION OF OIL AND GAS

WATER SHUTOFF TEST T.T. 7-22-83 No. T 184 241

Operator Xtra Energy Corp.

Well designation 50 Sec. 29, T. 4S, R. 13W, SB B.&M.

Field Wilmington, County Los Angeles was tested for water shutoff on 7/16/83. (Name) G. Muggelberg, representative of the supervisor, was present from 1330 to 1430. Also present were Floyd Million (D.E.)

Casing record of well:

16"dr 90'; 10 3/4" cem 608'; 7" cem 3812', cp 3800', perf 3802' WSO. TD 3936' (drilling).

The operations were performed for the purpose of (D-1) 7" 3802'

☑ The 7 " shutoff at 3802 ' is approved.

☐ The seal between the _____" and _____" casings is approved.

☐ The operations are approved as indicating that all of the injection fluid is confined to the formations below _____' at this time.

Hole size: 9 7/8 " fr. 615 ' to 3936 '; _____" to _____';& _____" to _____'

Casing				Cemented			Top of Fill		Sqd. Away	Final Press	Test psi/min. Perfs.
Size	Wt.	Top	Bottom	Date	MO-Depth	Volume	Annulus	Casing			
7"	23#	Ø	3812'	7/15/83	Bump Plugs	311 sks	—	3733	—	1200	—
"	"	"	"	"	Pkr @ 3693'	100 sks	—	—	114cf	2750	3800'

Depth or interval tested Four 1/2" holes @ 3802

The hole was open to 3802 ' for test.

FORMATION TEST:

Packer(s) 3760 ' & — ' Tail 3780 ' Bean size 3/4 " Cushion Ø

IHP 1561 IFP 137 FFP 137 FHP 1476

Blow Moderate 60 MM.

Open for test 1 Hr. Ø min. Fluid entry 270' gas cut mud

BAILING TEST:

The hole fluid was bailed to _____', at _____ on _____ 19__.

The hole fluid was found at _____', at _____ on _____ 19__.
(time)

PRODUCTION TEST:

Gauge/meter reading _____ on _____ 19__, at _____ pump depth _____' Engr. _____

Gauge/meter reading _____ on _____ 19__, at _____ Engr. _____

Fluid level _____' surveyed on _____ 19__, reviewed (witnessed) by _____

Total fluid produced, Bbls. _____ Net oil _____ Water _____

Rate: _____ B/D oil, _____ B/D water, _____ % water cut

INJECTION SURVEY:

RA/Spinner/Temperature survey run at _____ B/D & _____ psi on _____ 19__,

fluid confined below _____' (Packer depth _____')

16" dr 90'

DEFICIENCIES—TO BE CORRECTED

None

DEFICIENCIES—CORRECTED

One wet test

CONTRACTOR

Cal Pacific Drilling Co.

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION

No. T 183-520

DIVISION OF OIL AND GAS

Report on Operations

SEC. 3606 WELL

John D. Carmichael, Agent
XTRA ENERGY CORPORATION
Box "9"
Signal Hill, CA 90801

Long Beach Calif.
July 25, 1983

Your operations at well 50, API No. 037-22884,
Sec. 29, T. 4S, R. 13W S.B. B.& M. Wilmington Field, in Los Angeles County,
were witnessed on 7/9/83. R. Navia, Engineer, representative of
the supervisor, was present from 0530 to 0630. There were also present R. Napier, Drilling Foreman
Present condition of well: 16" dr 90'; 10-3/4" cem 608', TD 615' (Drilling).

The operations were performed for the purpose of testing the blowout prevention equipment and installation.

DECISION: APPROVED

NOTE: DEFICIENCIES TO BE CORRECTED
NONE

DEFICIENCIES CORRECTED
NONE

CONTRACTOR - Cal Pacific Drilling Co.

RN:csm

cc: Update

ACTING State Oil and Gas Supervisor
By S. I. CORDOVA

ACTING Deputy Supervisor
V.F. GAEDE

OG108(12-80-15M)

DIVISION OF OIL AND GAS
BLOWOUT PREVENTION EQUIPMENT MEMO

R1 7-22-83

T 16

Operator Tra Energy Corp. Well 50 Field Wilmington County LA

VISITS:	Date	Engineer	Time		Operator's Rep.	Title
1st	7/9/83	R. Navia	0530	to 0630	R. Napier	DF
2nd				to		

Casing record of well: 16" dv 90'; 10¾" cem 608'. TD 615' (drilling).

OPERATION: Testing (inspecting) the blowout prevention equipment and installation.

DECISION: The blowout prevention equipment and installation are approved.

Proposed Well Opns: Drill MPSP: ____ psi

Hole size: 14¾" fr. 0' to 615', ____" to ____' & ____" to ____'

REQUIRED BOPE CLASS: III B 2M

CASING RECORD (BOPE ANCHOR STRING ONLY)					Cement Details	Top of Cement	
Size	Weight(s)	Grade (s)	Shoe at	CP at		Casing	Annulus
10¾"	40.5 #	J-55	608'		854 sx C/155 G (stab-in shoe)	652	Stc

BOP STACK							a	b	a/b	TEST DATA			
API Symb.	Ram Sz.	Mfr.	Model or Type	Size In.	Press. Rtg.	Date Last Overhaul	Gal. to Close	Rec.Time Min.	Calc.GPM Output	psi Drop to Close	Secs.to Close	Test Date	Test Press
A	12	Shaffer	—	12	3000	—						7/9	1000
Rd	4½	Shaffer	E	12	"	—						"	1000
Rd	CSO	Shaffer	B	12	"	—				Kept by E. Roady 7/6			1000

ACTUATING SYSTEM

Accum.Unit(s) Wkg.Press. 3000 psi
Total Rated Pump Output — gpm
Distance From Well Bore 100 ft.

	Mfr.	Accum. Cap.	Precharge
1	Koomy	90 gal.	1000 psi
2		gal.	psi

	CONTROL STATIONS	Elec.	Hyd.
X	Manif. at accum.unit		✓
X	Remote at Drlr's stn.	pneum.ctr	
	Other:		

	EMERG. BACKUP SYST.			Press.	Wkg.Fl.
X	N2 Cyl	No:2	Tpe:-	12100	— gal
	Other:			22150	— gal
				3	gal
				4	gal
				5	gal
				6	gal

AUXILIARY EQUIPMENT

		No.	Sz. (in)	Rated Press.	Connections Weld	Flan.	Thrd.	
X	Fill-Up Line							
X	Kill Line		2	3000		✓	✓	1000
X	Control Valve(s)	3				✓	✓	"
X	Check Valve(s)	1				✓		"
X	Auxil. Pump Connec.						✓	"
X	Choke Line		3			✓		"
X	Control Valve(s)	6				✓		"
X	Pressure Gauge					✓		
X	Adjustable Choke(s)	2	3			✓		"
X	Bleed Line		6			✓		
X	Upper Kelly Cock							1000
X	Lower Kelly Cock		4½					—
X	Standpipe Valve							1000
X	Standpipe Pressure Ga.							
X	Pipe Safety Valve		4½	✓				—
X	Internal Preventer		4½					—

	HOLE FLUID MONITORING EQUIPMENT	Alarm Aud.	Alarm Vis.	Class
X	Calibrated Mud Pit			A
X	Pit Level Indicator	✓	✓	B
X	Pump Stroke Counter	✓	✓	B
X	Pit Level Recorder	✓	✓	C
	Flow Sensor			C
	Mud Totalizer			C
	Calibrated Trip Tank			
	Other:			

REMARKS: ____

Hole Fluid Type	Weight	Storage-Pits
Clay base	9.6 ppg	350 bbl

OGD9 (2/82/DWRR/3M)

DEFICIENCIES—TO BE CORRECTED

None

DEFICIENCIES—CORRECTED

None

CONTRACTOR

Cal Pacific Drilling Co.

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION
DIVISION OF OIL AND GAS

No. P 183-407

REPORT ON PROPOSED OPERATIONS

SEC. 3606 WELL

848 (field code)
03 (area code)
00 (new pool code)
-- (old pool code)

John D. Carmichael, Agent
XTRA ENERGY CORPORATION
Box "9"
Signal Hill, CA 90801

Long Beach, California
June 24, 1983

Your ____ proposal to drill well 50,
A.P.I. No. 037-22884, Section 29, T. 4S, R. 13W, S.B. B. & M.,
Wilmington field, F.B. I, Onshore area, Ranger pool,
Los Angeles County, dated 6/16/83, received 6/17/83 has been examined in conjunction with records filed in this office.

THE PROPOSAL IS APPROVED PROVIDED:

1. Blowout prevention equipment equivalent to this Division's Class IIIB-2M requirements, or better, shall be installed and maintained in operating condition.
2. Drilling fluid of a quality and in sufficient quantity to control all subsurface conditions in order to prevent blowouts shall be used.
3. Sufficient cement shall be used to fill back of the 7" casing to reach above the base of the fresh waters which is at approx. 1700'.
4. This Division shall be consulted and a supplementary notice may be required before making any changes in the proposed program.
5. The provisions of Sec. 3606 relating to derricks and subsurface spacing shall be followed.
6. A directional survey shall be made and filed with this Division.
7. THIS DIVISION SHALL BE NOTIFIED:
   a. To witness a test of the installed blowout prevention equipment prior to drilling out cement in the shoe of the 10-3/4" casing.
   b. To witness a test of the effectiveness of the 7" shut-off above the Ranger zone.

RCM:csm

cc: Update

BLANKET BOND

M. G. MEFFERD, State Oil and Gas Supervisor

By V.F. GAEDE, ACTING *Deputy Supervisor*

A copy of this report and the proposal must be posted at the well site prior to commencing operations.

Records for work done under this permit are due within 60 days after the work has been completed or the operations have been suspended.

OG111 (10/DWRR/5M)

OG

Sec. 3606

RESOURCES AGENCY OF CALIFORNIA
DEPARTMENT OF CONSERVATION

DIVISION OF OIL AND GAS

Notice of Intention to Drill New Well

C.E.Q.A. INFORMATION			
EXEMPT ☒ CLASS____	NEG. DEC. ☐ S.C.H. NO.____	E.I.R. ☐ S.C.H. NO.____	DOCUMENT NOT REQUIRED BY LOCAL JURISDICTION ☐
See Reverse Side			

FOR DIVISION USE ONLY					
MAP	MAP BOOK	CARDS	BOND	FORMS 114	FORMS 121
121	W	6/20/83	TB	6/23/83	6/16/83

W 6/20/83

In compliance with Section 3203, Division 3, Public Resources Code, notice is hereby given that it is our intention to commence drilling well # 50, API No. 037 - 22884 (Assigned by Division),

Sec. 29, T. 4S, R. 13W, S.B. B. & M., Wilmington Field, Los Angeles County.

Legal description of mineral-right lease, consisting of _____ acres, is as follows: _____ (Attach map or plat to scale)

Map previously submitted.

Do mineral and surface leases coincide? Yes____ No x. If answer is no, attach legal description of both surface and mineral leases, and map or plat to scale.

Location of well 497 feet N (Direction) ~~along section/property line~~ (Cross out one) and 827 feet E (Direction)

at right angles to said line from the ~~corner of section/property~~ (Cross out one) intersection of the centerlines of Main Street and Lomita Blvd.

Is this a critical well according to the definition on the reverse side of this form? Yes ☒ No ☐

If well is to be directionally drilled, show proposed coordinates (from surface location) at total depth: 872 feet S (Direction) and 1375 feet E (Direction)

Elevation of ground above sea level 39 feet.

All depth measurements taken from top of Kelly Bushing (Derrick Floor, Rotary Table, or Kelly Bushing) that is 22 feet above ground.

PROPOSED CASING PROGRAM

SIZE OF CASING INCHES API	WEIGHT	GRADE AND TYPE	TOP	BOTTOM	CEMENTING DEPTHS	CALCULATED FILL BEHIND CASING (Linear Feet)
10 3/4"	40.5#	K-55	Surf	600'	600'	600'
7"	23#	K-55	Surf	3734'	3734'	1984'
5"	18#	K-55	3664'	3884'	wire wrapped "pipeless" screen with 0.012" slot.	

(A complete drilling program is preferred and may be submitted in lieu of the above program.)

Intended zone(s) of completion FB I Ranger, 3230', SS, 1200 psi (Name, depth, and expected pressure) Estimated total depth 3884'

It is understood that if changes in this plan become necessary we are to notify you immediately.

Name of Operator	Type of Organization (Corporation, Partnership, Individual, etc.)	
Xtra Energy Corp.	Corporation	
Address	**City**	**Zip Code**
2501 Cherry Avenue Suite 270	Signal Hill	90806
Telephone Number / **Name of Person Filing Notice**	**Signature**	**Date**
(213)424-8549 / John D. Carmichael	John D. Carmichael	6/16/83

This notice and indemnity or cash bond shall be filed, and approval given, before drilling begins. If operations have not commenced within one year of receipt of the notice, this notice will be considered cancelled.

OG105 (1/82/DWRR/5M)

Information for compliance with the California Environmental Quality Act of 1970 (C.E.Q.A.).

If an environmental document has been prepared by the lead agency, please submit a copy of the document with this notice *or* supply the following information:

Lead Agency: City of Carson

Lead Agency Contact Person: Joel Miller

Address: PO Box 6234

Carson CA 90749

Phone: (213) 830-7600

FOR DIVISION USE ONLY
District review of environmental document (if applicable)? Yes ☐ No ☐
Remarks:

CRITICAL WELL

As defined in the California Administrative Code, Title 14, Section 1720(a), "Critical well" means a well within:

(1) 300 feet of the following:
(A) Any building intended for human occupancy that is not necessary to the operation of the well; or
(B) Any airport runway.
(2) 100 feet of the following:
(A) Any dedicated public street, highway, or nearest rail of an operating railway that is in general use;
(B) Any navigable body of water or watercourse perennially covered by water;
(C) Any public recreational facility such as a golf course, amusement park, picnic ground, campground, or any other area of periodic high-density population; or
(D) Any officially recognized wildlife preserve.

Exceptions or additions to this definition may be established by the supervisor upon his own judgment or upon written request of an operator. This written request shall contain justification for such an exception.

XTRA ENERGY CORPORATION

PROGRAM FOR DRILLING

WELL No. 50

Reference Point: KB which is 22' above G. E.

Surface Location: Lambert Coordinates N-4,039,625 E-4,205,428

Bottom Hole Location: Lambert Coordinates N-4,038,753 E-4,206,803

Elevation: 39' GE + 22' KB = 61'

Proposed Casing Program:

10-3/4" 40.5 # to be cemented at 600'
7 " 23 # to be cemented at 3734'
5 " 18 # to be hung at 3884', top @ 3664'.

Perfs: 3754' to 3884' Wire wrapped pipeless Johnson Screen liner with 0.012" slots.

Proposed Hole Size:

0' to 600' 14-3/4" hole
600' to 3884' 9-7/8" hole
3734' to 3884' 9-7/8" hole to be underreamed to 12".

Proposed Total Depth: 3884'

Directional Program

Deflect hole at 625' and increase inclination at 4°/100' in a S 57° 37' E direction to 38° at 3734'. Maintain 38° inclination to a depth of 3884'. Target is a 100' diameter circle with its center 872' South and 1375' East of the surface site. A total displacement of 1629'.

Mud Program

1. For drilling from surface to 600', use a safe fresh water clay base mud.

2. For drilling from 600' to 3884', use a fresh water clay base mud with the following properties.

a.	Weight	72 #/CF
b	Fluid loss	5 cc
c.	P.V.	8 - 14 cps
d.	YP	4 - 6#/100 sq. ft.
e.	Funnel vis	38 - 42"
f.	Solids	12%

3. For underreaming 9-7/8" hole to 12", use a polymer mud with the following properties.

a.	Weight	72#/CF
b.	P.V.	12 - 18 cps
c.	YP	4 - 6 #/100 sq. ft.
d.	Funnel vis	34 - 38"
e.	Solids	Minimum
f.	KCl (KCl)	4%

BOP Requirements

1. Bag type - Hydraulic 10" - 3000. 3000 psi WOG.

2. Ram type - double, hydraulic, 10" - 3000, 3000 psi WOG.

3. Accumulator - 80 gallon with dual controls.

Program

1. Install 16" conductor pipe to ± 40'.

2. Move in and rig up rotary equipment.

3. Drill 14-3/4" hole to 600'.

4. Run 10-3/4", 40.5#, J-55 casing to 600'. Casing to be fitted with a B & W stab-in shoe and centralizers on 1st, 2nd and 3rd joints. Cement 10-3/4" casing with 300 sacks of API class "G" cement mixed 1:1 with peralites and 4% Gel followed by enough neat "G" cement to get cement returns. All cement to be mixed with 2% $CaCl_2$.

5. Install wellhead and BOP. Representative of D.O.G. to witness pressure test of B.O.P.

6. Run 9-7/8" bit and clean out to 600'. Drill 9-7/8" hole to 3884'.

7. Run Induction electric log from total depth to the shoe of the 10-3/4" casing. Use 20 ohm scale. Two field prints are required including one with 5" scale.

8. Run 7", 23#, K-55 casing to 3734'. Casing to be fitted with a Baker basket shoe and Baker float collar 2 joints above shoe. Centralizers to be installed on 1st, 2nd, 4th and 6th joints above shoe. Cement 7" casing as follows: 300 linear feet (80 CF) of "mud sweep" or equivalent followed by 211 sacks of class G cement mixed 1:1:4 (cement:perlite:gel) mixed with 2% $CaCl_2$, followed by 100 sacks of G cement, neat. Cement to reach 1750' TVD. Land Casing.

9. After 24 hours, clean out cement to 3724' (± 10' above shoe). Run combination jet perforator and casing tester. Shoot 4 holes as directed and test water shut off. Results of WSO test to be witnessed by representative of California Division of Oil and Gas.

10. Run 6-1/4" bit, drill out shoe at 3734' and clean out to 3884'.

11 Change over to Polymer completion fluid.

12. Underream 9-7/8" hole to 12" from the 7" casing shoe to total depth. Run Caliper log.

13. Make up and run 5", 18#, K-55 liner as directed.

14. Gravel pack 5" x 12" annulus with 95 CF of 20 - 40 mesh gravel.

15. Displace Polymer mud in hole with salt water and close in.

16. Move out rotary equipment.

No. 50
TLL:JDC:sc
6-15-83